



Weighing Technology

A Higher Level of Precision... A Higher Level of Performance

APM

SERIES

NTEP / Measurement Canada Approved Portable Bench Scale

- ✓ Economical
- ✓ Light Weight
- ✓ Large Backlit Display
- ✓ Versatile



Manufactured for Intelligent Weighing Technology, Inc. in an ISO 9001 certified facility

APM

SERIES



NTEP/Measurement Canada Approved Portable Bench Scale

Model	APM-15	APM-30	APM-60	APM-150
Capacity	15 kg / 30 lb	30 kg / 60 lb	60 kg / 150 lb	150 kg / 300 lb
Readability	0.005 kg / 0.01 lb	0.01 kg / 0.02 lb	0.02 kg / 0.05 lb	0.05 kg / 0.1 lb
Divisions	3,000			
Stabilization Time (seconds)	<1.5			
Weighing Units	kg, lb, accumulation			
Tare Range	4.995 kg	9.99 kg	19.98 kg	49.95 kg
Power Source	Built-in rechargeable battery or external power adapter (included)			
Construction	Stainless steel pan, ABS housing			
Display	1 inch / 25.4 mm wide viewing angle backlit LCD			
Platform Size (W x D x H)	11 x 13 x 4.13 inches / 280 x 330 x 105 mm			
Overall Dimensions (W x D x H)	Platform mounted indicator: 11 x 16.5 x 4.1 inches / 280 x 420 x 105 mm With pillar: 11 x 13 x 24.8 inches / 280 x 330 x 630 mm			
Operating Environment	32° F to 104 ° F non condensing R.H. ≤ 85%			
Net Weight	13.4 lb / 6.1 kg			
Shipping Weight	16 lb / 7.3 kg			
Approvals	NTEP CoC # 03 - 055, Measurement Canada Approval # AM-5544			
Options	Stainless steel pillar, Oxyweigher™ transport kit, Traveler™ transport case, Traveler™ carrying handle			

Features	Benefits
Large LCD display with backlight	Gives excellent readability in sunlight, ideal for outdoor use
Heavy duty construction	Will withstand harsh industrial operation
Light weight	Ideal for portability, only 13.4 lb
Low profile	Easy to load and unload platform – only 4.1 inches / 105 mm high
Built in rechargeable battery or external power adapter	Portability – battery lasts a minimum of 150 hours (without backlight)
Reads in kg and lb	Flexibility of operation
Zero tracking	Ensures you always start weighing at zero
Automatic power save	Conserves battery power
Low battery indicator	Alerts you to charge the battery, saving downtime
Easy calibration function	Ensures accuracy
Adjustable feet	Balance remains level for accurate results on uneven working surfaces - Anti-slip
Wide angle LCD display	Can be seen from a wide viewing range in sunshine, ideal for outdoor use
Options for display: platform, pillar or wall mounted (3 ft of cable supplied)	Flexibility of operation and position
Selectable auto tare function	Allows the first article on the platter to be automatically tared
Gravitational correction software	Enables you to input different G acceleration factors



Intelligent Weighing Technology, Inc.
www.intelligentwt.com

Rev: APM 6/12