



Weighing Technology

A Higher Level of Precision...A Higher Level of Performance


MII

SERIES



Compact High Resolution Toploading Scale

- Ultra Portable
- Quality Control
- Backlit Display
- 9 Volt Battery
- RS 232 Interface



Manufactured in Democratic Taiwan for Intelligent Weighing Technology, Inc. in an ISO 9001 certified facility

Model	MII-600	MII-3000	MII-6000
Capacity	600 g / 21 oz	3,000 g / 6 lb	6,000 g / 13 lb
Readability	0.1 g / 0.005 oz	0.5 g / 0.02 oz	1 g / 0.05 oz
Divisions	6,000		
Weighing Units	g / oz	g / lb:oz	
Stabilization Time	< 2 seconds		
Tare Range	To capacity by subtraction		
Power Source	1 x 9 volt battery (not included) or external power adapter (included)		
Construction	Stainless steel pan and ABS housing		
Display	0.79 inches / 20 mm wide viewing angle LCD with backlight		
Pan Size (W x D)	8 x 5.1 inches / 205 x 130 mm		
Overall Dimensions (W x D x H)	8 x 7.9 x 2.3 inches / 205 x 200 x 58 mm		
Operating Environment	32 °F to 104 °F non condensing R.H. ≤ 85%		
Connectivity	RS 232 configurable interface		
Net Weight	2.5 lb / 1.12 kg		
Shipping Weight	5 lb / 2.3 kg		
Options	Large Traveler transport case, Printers		

Features	Benefits
6,000 divisions	Allows for high accuracy in general purpose weighing
Low profile, compact size	Uses less counter space
Reads in grams and pounds:ounces	Flexibility of operation
Battery powered. External power adapter included	Totally portable
Tactile keypad	Easy to enter information on positive keypad
Zero tracking	Ensures that you always start weighing at zero
Zero indicator	Informs you when the balance is ready to weigh
One touch zero / tare	Easy to operate
Automatic power save	Conserves battery power
Low battery indicator	Alerts you to charge the battery, saving downtime
Easy calibration function	Ensures accuracy
Wide angle LCD display with backlight	Can be seen from a wide viewing range
RS 232 configurable interface	Allows communication with peripheral data collection and printing instruments